

U.S. Patent Application Serial No. 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

RECEIVED  
CENTRAL FAX CENTER  
MAY 01 2007

**Listing of Claims:**

1. (currently amended): A method for providing an injection from a medical device, comprising the steps of:

providing a medical device comprising a barrel, a retractable needle, a mounting stem having a connector that is cooperable with a cartridge containing a quantity of medicinal fluid, wherein the mounting stem is spaced apart from the barrel to provide an annular passage, the mounting stem extending longitudinally within the barrel along a majority of a length of the barrel, and the device comprises an arm radial member connected with the mounting stem and releasably engaging a recess in the barrel to retain the stem in a fixed axial position relative to the barrel during an injection;

providing a cartridge containing a quantity of medicinal fluid, comprising a fluid container and a seal comprising a connector cooperable with the connector on the stem;

attaching the cartridge to the mounting stem by connecting the seal connector with the stem connector;

displacing the fluid container forwardly through the annular passage until the fluid container engages the ~~arm~~ radial member, whereby while the fluid container is displaced forwardly the stem maintains the seal in a fixed axial position, relative to the barrel;

displacing the fluid container further forwardly after the fluid container engages the ~~arm~~ radial member so that the fluid container displaces the ~~arm~~ radial member.

U.S. Patent Application Serial No. 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

disengaging the ~~arm~~ radial member from the recess and effecting release of the needle; and

retracting the needle after release ~~by means of~~ via a biasing element biasing the needle rearwardly.

2. (original): The method of claim 1 comprising the step of piercing the seal to provide fluid communication between the fluid container and the needle.

3. (original): The method of claim 1 wherein the fluid container comprises a fluid chamber having a length and extending from the rearward end of the seal to the rearward end of the container, and wherein the step of displacing the fluid container comprises displacing the fluid container forwardly a distance that is substantially similar to the length of the fluid chamber.

4. (currently amended): A method for providing an injection from a medical device, comprising the steps of:

providing a medical device comprising a barrel, a needle having a sharpened tip projecting forwardly from the barrel, a biasing element biasing the needle rearwardly, and a mounting stem disposed within the barrel;

releasably retaining the mounting stem in a fixed axial position relative to the barrel by ~~an arm~~ a radial member attached to the mounting stem and engaging a recess in the barrel;

U.S. Patent Application Serial No 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

providing a cartridge comprising a fluid container containing a quantity of medicinal fluid and a slidable seal forming a fluid-tight seal with the container;

attaching the seal to the stem to connect the cartridge to the medical device;

retaining the seal in a fixed axial position relative to the barrel while displacing the fluid container forwardly over the seal to expel the fluid from the container and through the needle; and

displacing the fluid container further forwardly after the fluid container engages the ~~arm~~ radial member, thereby disengaging the ~~arm~~ radial member from the recess and causing the needle to be released for retraction.

5. (original): The method of claim 4 comprising the step of retracting the needle so that the sharpened tip of the needle is retracted into the barrel.

6. (original): The method of claim 4 comprising the step of piercing the seal to provide fluid communication between the fluid container and the needle.

7. (original): The method of claim 4 wherein the fluid container comprises a fluid chamber having a length that extends from the rearward end of the seal to the rearward end of the container, and wherein the step of retaining the seal while displacing the fluid container comprises displacing the fluid container forwardly a distance that is substantially similar to the length of the fluid chamber.

U S Patent Application Serial No. 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

8. (currently amended): A medical device for providing an injection of fluid, comprising:

a hollow housing having a central axis;

an ampoule of fluid comprising a container having a length, an open end forming a rim and a plug sealing the open end, wherein the container comprises a fluid chamber having a length that extends from a rearward end of the plug to the rearward end of the container;

a needle having a sharpened tip operable between a projecting position in which the sharpened tip projects forwardly from the housing and a retracted position in which the sharpened tip is shielded against inadvertent contact;

a biasing element biasing the needle toward the retracted position;

a stem disposed within the housing configured to matingly engage the ampoule plug to attach the plug to the stem wherein the stem is operable in connection with the ampoule to provide an injection of fluid through the needle from the ampoule by displacing the ampoule forwardly relative to the stem; and

a latch first radial member disposed in a distal portion of the housing, the first radial member releasably retaining the stem at a fixed axial position during the injection wherein when the ampoule is mounted on the stem, the latch first radial member is spaced from the rim of the container a distance substantially similar to the length of the fluid chamber so that at the end of the injection the ampoule engages the latch first radial member; and

U.S. Patent Application Serial No. 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

a second radial member disposed in a proximal portion of the housing, the second radial member maintaining the stem aligned parallel with the axis of the housing;

wherein after the ampoule engages the ~~latch~~ first radial member, continued forward displacement of the ampoule operates to effectuate release of the needle.

9. (currently amended): The medical device of claim 8 wherein the housing comprises a recess cooperable with the ~~latch~~ first radial member.

10. (cancelled)

11. (original) The medical device of claim 8 comprising a needle retainer releasably retaining the needle in the extended position against the bias of the spring.

12. (original) The medical device of claim 8 wherein the plug has a piercable wall for providing access to the medicine in the ampoule.

13. (original) The medical device of claim 12 comprising a piercing element projecting from the stem that is operable to pierce the wall of the plug.

14. (original) The medical device of claim 13 wherein the piercing element is in fluid communication with the sharpened tip.

U.S. Patent Application Serial No. 10/724,663  
Amendment dated May 1, 2007  
Reply to Office Action of March 7, 2007

15. (original) The medical device of claim 8 wherein the container comprises a closed end forming a manually operable surface for displacing the container relative to the housing.

16. (original) The medical device of claim 8 wherein the rearward end of the housing is open, forming a socket for receiving the ampoule.

17. (new): The medical device of claim 8 wherein the second radial member is configured to flex to permit the container to pass between the stem and the hollow housing during forward displacement of the ampoule.

18. (new): The method of claim 1 wherein the medical device comprises a second radial member disposed in a proximal portion of the barrel, the second radial member retaining the stem in a fixed axial position relative to the barrel.